



Sweeper and Snow Plow



Tiger Push Frame - another multiuse attachment adding versatility to your Tiger mowing product line

INTERCHANGEABILITY

The Tiger Sweeper / Snow Plow comes as a complete interchangeable system. Utilizing Tiger's push frame that mounts to the front of the tractor, you can now change from sweeper to snow plow in minutes and use the same mounting system for each.

Get those tough jobs done in a hurry with these handy attachments.




DURABILITY INNOVATION
COMMITMENT

Tiger Features

Performance. Power.

Set up your tractor for more options with the Tiger heavy duty push frame. Built from 3" x 4" steel, giving you the performance and power to take on the toughest jobs.

The 11' moldboard front plow is made from 10 mm steel and features a front blade that is 30" in height, equipped with plasma cut steel ribs and six (6) tension trip springs. Dual Cylinders for angling left or right along with a Single Lift Cylinder come as standard equipment.



PLUG & PLAY
BULKHEAD FOR
QUICK DISCONNECT



Hardworking. Versatile.

Built tough with better control to meet the ever changing needs of our customers.

Tiger's 8' sweeper attachment mounts to the front of your tractor and allows debris to be swept away quickly and easily. The Heavy Duty brush is constructed of 50% Poly and 50% wafer core. The sweeper drive is powered by two hydraulic motors and features hydraulic lift and angle control up to 30° left or right. Brush core is reversible for even brush wear.

The universal sweeper or snow plow attachments connect easily to Tiger's base Push Frame that is mounted to the front of the tractor. This can be added to any existing Tiger mowing product or a bare tractor with the installation of weldment push frame tabs and hydraulic controls. Our system allows interchangeability of either attachment in minutes.

	SWEeper	SNOW PLOW
Drive	Tractor Hydraulics	Tractor Hydraulics
Motor	Dual Motors	
Width	8 Feet wide	11 feet wide
Angle	30 degrees Left and Right	30 degrees Left and Right
Height	32" Brush Diameter	30" Blade Height
Hydraulic Range	20-36 GPM @ 3,500 PSI	
Shipping Weight	814 lbs.	1180 lbs.
Cutting Edges		AASHTO 1/2" thick cutting edges
Transport Width	8' 6"	9' @ 30° angle of blade
Controls	Tractor remotes	Tractor remotes



WILDKAT/SWEEPER



SIDE ROTARY/SNOW PLOW

Dealer Info:

Tiger Corporation
3301 North Louise Ave.
Sioux Falls, SD, USA 57107
800.843.6849
www.tigermowers.com



An Alamo Group® Company
Specifications are subject to change. Optional equipment maybe shown.

Meets All Applicable ANSI / SAE Test Standards.
© 2017 Tiger Corporation. All Rights Reserved. Printed in the USA.



MADE WITH PRIDE IN THE USA